



# Product Specification

M240HTD01.0

AU OPTRONICS CORPORATION

( ) Preliminary Specification

(V) Final Specification

Module	24" Color TFT-LCD
Model Name	M240HTD01.0

<table><tr><td>Customer</td><td>Date</td></tr><tr><td><hr/></td><td><hr/></td></tr><tr><td>Approved by</td><td></td></tr><tr><td><hr/></td><td><hr/></td></tr></table>	Customer	Date	<hr/>	<hr/>	Approved by		<hr/>	<hr/>	<table><tr><td>Approved by</td><td>Date</td></tr><tr><td><u>Kyle Su</u></td><td><u>2012/7/20</u></td></tr><tr><td>Prepared by</td><td></td></tr><tr><td><u>JiaHauJean</u></td><td><u>2012/7/20</u></td></tr></table>	Approved by	Date	<u>Kyle Su</u>	<u>2012/7/20</u>	Prepared by		<u>JiaHauJean</u>	<u>2012/7/20</u>
Customer	Date																
<hr/>	<hr/>																
Approved by																	
<hr/>	<hr/>																
Approved by	Date																
<u>Kyle Su</u>	<u>2012/7/20</u>																
Prepared by																	
<u>JiaHauJean</u>	<u>2012/7/20</u>																
Note: This Specification is subject to change without notice.	Desktop Display Business Group / AU Optronics corporation																



# Product Specification

M240HTD01.0

AU OPTRONICS CORPORATION

## Contents

<b>1.0 Handling Precautions.....</b>	<b>4</b>
<b>2.0 General Description .....</b>	<b>5</b>
2.1 Display Characteristics .....	5
2.2 Optical Characteristics .....	6
<b>3.0 Functional Block Diagram .....</b>	<b>10</b>
<b>4.0 Absolute Maximum Ratings.....</b>	<b>11</b>
4.1 TFT LCD Module .....	11
4.2 Backlight Unit .....	11
4.3 Absolute Ratings of Environment .....	11
<b>5.0 Electrical characteristics .....</b>	<b>12</b>
5.1 TFT LCD Module .....	12
5.1.1 Power Specification .....	12
5.1.2 Signal Electrical Characteristics .....	13
5.2 Backlight Unit .....	15
<b>6.0 Signal Characteristic .....</b>	<b>17</b>
6.1 Pixel Format Image .....	17
6.2 The input data format.....	17
6.3 Signal Description.....	18
6.4 Timing Characteristics .....	20
6.5 Timing diagram.....	21
6.6 Power ON/OFF Sequence .....	22
<b>7.0 Connector &amp; Pin Assignment.....</b>	<b>23</b>
7.1 TFT LCD Module .....	23
7.1.1 Pin Assignment .....	23
7.2 Connector on Backlight Unit. ....	24
7.2.1 Signal for LED light bar connector.....	24
<b>8.0 Reliability Test .....</b>	<b>25</b>
<b>9.0 Shipping Label .....</b>	<b>26</b>
<b>10.0 Mechanical Characteristics.....</b>	<b>27</b>
<b>11.0 Packing Specification .....</b>	<b>29</b>



# Product Specification

M240HTD01.0

AU OPTRONICS CORPORATION

## Record of Revision

Version and Date	Page	Old description	New Description	Remark
0.1 2011/09/30		First Version		
0.2 2012/2/24		Second Version		
0.3 2012/4/23		Third Version		
1.0 2012/7/20		Final Version		



# Product Specification

M240HTD01.0

AU OPTRONICS CORPORATION

## 1.0 Handling Precautions

- 1) Since front polarizer is easily damaged, pay attention not to scratch it.
- 2) Be sure to turn off power supply when inserting or disconnecting from input connector.
- 3) Wipe off water drop immediately. Long contact with water may cause discoloration or spots.
- 4) When the panel surface is soiled, wipe it with absorbent cotton or other soft cloth.
- 5) Since the panel is made of glass, it may break or crack if dropped or bumped on hard surface.
- 6) Since CMOS LSI is used in this module, take care of static electricity and insure human earth when handling.
- 7) Do not open or modify the Module Assembly.
- 8) Do not press the reflector sheet at the back of the module to any directions.
- 9) In case if a Module has to be put back into the packing container slot after once it was taken out from the container, do not press the center of the LED lightbar edge. Instead, press at the far ends of the LED light bar edge softly. Otherwise the TFT Module may be damaged.
- 10) At the insertion or removal of the Signal Interface Connector, be sure not to rotate nor tilt the Interface Connector of the TFT Module.
- 11) After installation of the TFT Module into an enclosure, do not twist nor bend the TFT Module even momentary. At designing the enclosure, it should be taken into consideration that no bending/twisting forces are applied to the TFT Module from outside. Otherwise the TFT Module may be damaged.
- 12) Small amount of materials having no flammability grade is used in the LCD module. The LCD module should be supplied by power complied with requirements of Limited Power Source (IEC60950 or UL1950), or be applied exemption.
- 13) Avoid touching COF position while doing mechanical design.
- 14) While storing modules as spares for a long time, the following precautions are necessary:
  - Store modules in a dark place. Do not expose them to sunlight or fluorescent light.
  - Keep the temperature between 5°C and 35°C at normal humidity.



# Product Specification

M240HTD01.0

AU OPTRONICS CORPORATION

## 2.0 General Description

This specification applies to the 24 inch-FHD Color a-Si TFT-LCD Module M240HTD01. The display supports the FHD - 1920(H) x 1080(V) screen format and 16.7M colors (RGB 8-bits). The light source of this TFT-LCD module is W-LED. All input signals are 2-channel LVDS interface and this module doesn't contain a driver for backlight.

## 2.1 Display Characteristics

The following items are characteristics summary on the table under 25°C condition:

ITEMS	Unit	SPECIFICATIONS
Screen Diagonal	[mm]	609.7(24.0")
Active Area	[mm]	531.36 (H) x 298.89 (V)
Pixels H x V		1920(x3) x 1080
Pixel Pitch	[um]	276.75 (per one triad) x276.75
Pixel Arrangement		R.G.B. Vertical Stripe
Display Mode		TN Mode, Normally White
White Luminance ( Center )	[cd/m <sup>2</sup> ]	300 cd/m <sup>2</sup> (Typ.)
Contrast Ratio		1000(Typ.)
Resolution(3D)		~(1920x1080)/2
Optical Response Time	[msec]	5ms (Typ., on/off)
Nominal Input Voltage VDD	[Volt]	+5.0 V (Typ)
Power Consumption (VDD line + LED line)	[Watt]	Total = 21.59 watt VDD line : PDD(typ), All black pattern at 60Hz = 7 W LED line : PBLU (typ) =14.59 W
Weight	[Grams]	3050 typ.
Physical Size	[mm]	559.0(H)x324.2(V)x16.5(D)(typ.)
Electrical Interface		Dual channel LVDS
Support Color		16.7M colors (RGB 8-bit)
Surface Treatment		Anti-Glare, 3H
Temperature Range		
Operating	[°C]	0 to +50
Storage (Shipping)	[°C]	-20 to +60
RoHS Compliance		RoHS Compliance
TCO Compliance		TCO 5.1 Compliance



## Product Specification

M240HTD01.0

AU OPTRONICS CORPORATION

## 2.2 Optical Characteristics

The optical characteristics are measured under stable conditions at 25°C:

Item	Unit	Conditions	Min.	Typ.	Max.	Note
Viewing Angle(2D)	[degree]	Horizontal (Right) CR = 10 (Left)	150	170	- -	2
		Vertical (Up) CR = 10 (Down)	140	160	- -	
Viewing Angle(3D)	[degree]	Horizontal (Right) Cross talk<15% (Left)		20 20		2
		Vertical (Upper) Cross talk<15% (Lower) (viewdistance 60cm from camera center)		11 11		
Viewing Distance	[cm]		60		100	
Contrast ratio		Normal Direction	600	1000		3
Response Time	[msec]	Raising Time (T <sub>rR</sub> )	-	3.5	7.4	4
		Falling Time (T <sub>rF</sub> )	-	1.5	2.6	
		Raising + Falling	-	5	10	
		Gray to Gray(16x16 avg.)				
Color / Chromaticity Coordinates (CIE)		Red x	0.612	0.642	0.672	5
		Red y	0.303	0.333	0.363	
		Green x	0.304	0.334	0.364	
		Green y	0.593	0.623	0.653	
		Blue x	0.125	0.155	0.185	
		Blue y	0.022	0.052	0.082	
Color Coordinates (CIE) White		White x	0.283	0.313	0.343	
		White y	0.299	0.329	0.359	
Central Luminance	[cd/m <sup>2</sup> ]		250	300	-	6
Luminance Uniformity	[%]		75	80	-	7
2D Crosstalk (in 60Hz)	[%]				1.5	8
Flicker	dB				-20	9




# Product Specification

M240HTD01.0

AU OPTRONICS CORPORATION


## Note 1: Measurement method

The LCD module should be stabilized at given temperature for 30 minutes to avoid abrupt temperature change during measuring (at surface 35°C). In order to stabilize the luminance, the measurement should be executed after lighting Backlight for 30 minutes in a stable, windless and dark room.



## Note 2: Definition of viewing angle measured by ELDIM (EZContrast 88)

Viewing angle is the measurement of contrast ratio  $\geq 10$ , at the screen center, over a 180° horizontal and 180° vertical range (off-normal viewing angles). The 180° viewing angle range is broken down as follows; 90° ( $\theta$ ) horizontal left and right and 90° ( $\phi$ ) vertical, high (up) and low (down). The measurement direction is typically perpendicular to the display surface with the screen rotated about its center to develop the desired measurement viewing angle.



above for viewing angle under 3D mode is defined as below:





# Product Specification

M240HTD01.0

AU OPTRONICS CORPORATION

$$\text{Crosstalk\_Left}(\%) = L_{\text{black}} R_{\text{white}} / L_{\text{white}} R_{\text{black}}$$

Where

**Crosstalk\_Left(%)** means left eye crosstalk;

**L<sub>black</sub>** means left eye black signal;

**R<sub>white</sub>** means right eye white signal;

**L<sub>white</sub>** means left eye white signal;


**R<sub>black</sub>** means right eye black signal;

Right eye crosstalk is defined by analogy.

**Note 3: Contrast ratio** is measured by TOPCON SR-3

**Note 4: Definition of Response time** measured by Westar TRD-100A

The output signals of photo detector are measured when the input signals are changed from “Full Black” to “Full White” (rising time,  $Tr_R$ ), and from “Full White” to “Full Black” (falling time,  $Tf_F$ ), respectively. The response time is interval between the 10% and 90% (1 frame at 60 Hz) of amplitudes.



$Tr_R + Tf_F = 5 \text{ msec (typ.)}$ .

Algorithm:  $|\text{Gray Level A} - \text{Gray Level B}| \geq 16$ , then the average gray to gray response time is 2 ms, (F= 60 Hz).

**Note 5: Color chromaticity and coordinates (CIE)** is measured by TOPCON SR-3

**Note 6: Central luminance** is measured by TOPCON SR-3

**Note 7: Luminance uniformity of these 9 points** is defined as below and measured by TOPCON SR-3






# Product Specification

AU OPTRONICS CORPORATION

M240HTD01.0



$$\text{Uniformity} = \frac{\text{Minimum Luminance in 9 points (1 - 9)}}{\text{Maximum Luminance in 9 Points (1 - 9)}}$$


**Note 8: Crosstalk is defined as below and measured by TOPCON SR-3**

$$CT = | YB - YA | / YA \times 100 (\%)$$


Where

YA = Luminance of measured location without gray level 0 pattern (cd/m2)

YB = Luminance of measured location with gray level 0 pattern (cd/m2)



**Note 9: Test Pattern: Subchecker Pattern measured by TOPCON SR-3**



Gray Level = L127



Gray Level = L0




# Product Specification

AU OPTRONICS CORPORATION

M240HTD01.0


Method: Record dBV & DC value with TRD-100



$$\text{Flicker (dB)} = 20 \log \frac{\text{AC Level(at 30 Hz)}}{\text{DC Level}}$$

## 3.0 Functional Block Diagram

The following diagram shows the functional block of the 24.0 inch Color TFT-LCD Module:



### I/F PCB Interface:

P-TWO 187060-4122

JAE FI-RE41S-HF

### Mating Type:

FI-RE41HL/CL



# Product Specification

M240HTD01.0

AU OPTRONICS CORPORATION

## 4.0 Absolute Maximum Ratings

Absolute maximum ratings of the module are as following:

### 4.1 TFT LCD Module

Item	Symbol	Min	Max	Unit	Conditions
Logic/LCD Drive Voltage	VDD	0	6.0	[Volt]	<b>Note 1,2</b>

### 4.2 Backlight Unit

Item	Symbol	Min	Max	Unit	Conditions
LED Forward Current	IRLED1		63	[mA]	<b>Note 1,2,5</b> 100% duty
	IRLED2				
	IRLED3				
	IRLED4				
LED Pulse Forward Current	IPLD1	-	150	[mA]	<b>Note 1,2,5</b> 10% duty @100Hz
	IPLD2				
	IPLD3				
	IPLD4				
LED forward Voltage variation (per string variation)	$\Delta V_f$	-	7.6	[Volt]	<b>Note 1,2</b>

### 4.3 Absolute Ratings of Environment

Item	Symbol	Min.	Max.	Unit	Conditions
Operating Temperature	TOP	0	+50	[°C]	<b>Note 3</b>
Glass Surface Temperature (Operation)	TGS		+65	[°C]	<b>Note3</b> <b>Note4</b>
Operation Humidity	HOP	5	90	[%RH]	<b>Note 3</b>
Storage Temperature	TST	-20	+60	[°C]	
Storage Humidity	HST	5	90	[%RH]	

**Note 1:** With in Ta (25 °C)

**Note 2:** Permanent damage to the device may occur if exceeding maximum values

**Note 3:** Temperature and relative humidity range are shown as the below figure.

1. 90% RH Max ( Ta ≤ 39°C)
2. Max wet-bulb temperature at 39°C or less. ( Ta ≤ 39°C)
3. No condensation

**Note 4:** Function Judged only


**Note 5:** IRLED1,2,3,4 and IPLD1,2,3,4 define as per strings LED current.



# Product Specification

AU OPTRONICS CORPORATION


M240HTD01.0



Operating Range



Storage Range



## 5.0 Electrical characteristics

### 5.1 TFT LCD Module

#### 5.1.1 Power Specification

Input power specifications are as following:

Symbol	Description	Min	Typ.	Max	Unit	Conditions
VDD	Logic/LCD Drive Voltage	4.5	5	5.5	[Volt]	+/-10%
IDD1	Input Current	-	1.2	1.36	[A]	VDD= 5.0V, All black Pattern at 60 Hz
		-	1.4	1.6	[A]	VDD= 5.0V, All black Pattern at 75 Hz
PDD1	VDD Power	-	6	7.5	[Watt]	VDD= 5.0V, All black Pattern at 60 Hz
		-	7	8.8	[Watt]	VDD= 5.0V, All black Pattern at 75 Hz
IRush	Inrush Current	-	-	3.5	[A]	<b>Note 1</b>
VDDrp	Allowable Logic/LCD Drive Ripple Voltage	-	-	500	[mV] p-p	VDD= 5.0V, All black Pattern at 75 Hz

**Note 1:** Measurement conditions:



The duration of rising time of power input is 470us.



## Product Specification

AU OPTRONICS CORPORATION

**M240HTD01.0**



### 5.1.2 Signal Electrical Characteristics

Input signals shall be low or Hi-Z state when VDD is off. Please refer to specifications of SN75LVDS82DGG (Texas Instruments) in detail.

**1. DC Characteristics of each signal are as following:**

Symbol	Parameter	Min	Typ	Max	Units	Condition
-	Differential Input High Threshold	-	-	+100	[mV]	$V_{CM} = 1.2V$ <b>Note 1</b>
VTL	Differential Input Low Threshold	-100	-	-	[mV]	$V_{CM} = 1.2V$ <b>Note 1</b>
VID	Input Differential Voltage	100	350	600	[mV]	<b>Note 1</b>
VCM	Differential Input Common Mode Voltage	VID  / 2	+1.2	2.4- VID  / 2	[V]	$V_{TH}-V_{TL} = 200MV$ (max) <b>Note 1</b>


**Note 1:** LVDS Signal Waveform



# Product Specification

AU OPTRONICS CORPORATION

M240HTD01.0








# Product Specification

M240HTD01.0

AU OPTRONICS CORPORATION

## 2. AC Characteristics

Description	Symbol	Min	Max	Unit	Note
Maximum deviation of input clock frequency during SSC	$F_{DEV}$	-	$\pm 1.5$	%	With Random Jitter
Maximum modulation frequency of input clock during SSC	$F_{MOD}$	-	20	KHz	







## Product Specification

M240HTD01.0

AU OPTRONICS CORPORATION

### 5.2 Backlight Unit

Parameter guideline for LED driving is under stable conditions at 25°C (Room Temperature):

Symbol	Parameter	Min.	Typ.	Max.	Unit	Note
IR <sub>LED</sub>	LED Operation Current	-	60	63	[mA] Note 1	<b>Note 1</b>
V <sub>LB</sub>	Light Bar Operation Voltage (for reference)	-	60.8	68.4	[Volt] Note 2	<b>Note 2</b>
P <sub>BLU</sub>	BLU Power consumption (for reference)	-	14.59	17.24	[Watt]	<b>Note 3</b>
LT <sub>LED</sub>	LED life Time (Typical)	30,000		-	[Hour] Note 3	<b>Note 4</b>

Each module consists of 76 pcs LED ( 4 strings x 19 pcs / string )

**Note 1:** The specified current is 100% duty of LED chip input current, IRLED1,2,3,4 define as per strings LED current.

**Note 2:** The value showed is one string operation voltage.

**Note 3:**  $P_{BLU} = V_{LED} * (IR_{LED1} + IR_{LED2} + IR_{LED3} + IR_{LED4})$

**Note 4:** Definition of life time: Brightness becomes to 50% of its original value. The minimum life time of LED unit is on the condition of IRLED = 60mA and 25±2°C (Room Temperature).



# Product Specification


M240HTD01.0

AU OPTRONICS CORPORATION


## 6.0 Signal Characteristic

### 6.1 Pixel Format Image

Following figure shows the relationship of the input signals and LCD pixel format.



### 6.2 The input data format



**Note 1:** R/G/B data 7:MSB, R/G/B data 0:LSB O = "Odd Pixel Data" E = "Even Pixel Data"



# Product Specification

M240HTD01.0

AU OPTRONICS CORPORATION

## 6.3 Signal Description

The module using one LVDS receiver SN75LVDS82(Texas Instruments). LVDS is a differential signal technology for LCD interface and high speed data transfer device. LVDS transmitters shall be SN75LVDS83(negative edge sampling). The first LVDS port(RxOxxx) transmits odd pixels while the second LVDS port(RxExxx) transmits even pixels.

PIN #	SIGNAL NAME	DESCRIPTION
1	RxOIN0-	Negative LVDS differential data input (Odd data)
2	RxOIN0+	Positive LVDS differential data input (Odd data)
3	RxOIN1-	Negative LVDS differential data input (Odd data)
4	RxOIN1+	Positive LVDS differential data input (Odd data)
5	RxOIN2-	Negative LVDS differential data input (Odd data, DSPTMG)
6	RxOIN2+	Positive LVDS differential data input (Odd data, DSPTMG)
7	GND	Power Ground
8	RxOCLK-	Negative LVDS differential clock input (Odd clock)
9	RxOCLK+	Positive LVDS differential clock input (Odd clock)
10	RxOIN3-	Negative LVDS differential data input (Odd data)
11	RxOIN3+	Positive LVDS differential data input (Odd data)
12	RxEIN0-	Negative LVDS differential data input (Even data)
13	RxEIN0+	Positive LVDS differential data input (Even data)
14	GND	Power Ground
15	RxEIN1-	Positive LVDS differential data input (Even data)
16	RxEIN1+	Negative LVDS differential data input (Even data)
17	GND	Power Ground
18	RxEIN2-	Negative LVDS differential data input (Even data)
19	RxEIN2+	Positive LVDS differential data input (Even data)
20	RxECLK-	Negative LVDS differential clock input (Even clock)
21	RxECLK+	Positive LVDS differential clock input (Even clock)
22	RxEIN3-	Negative LVDS differential data input (Even data)
23	RxEIN3+	Positive LVDS differential data input (Even data)
24	GND	Power Ground
25	NC	No connection (for AUO test only. Do not connect)
26	NC	No connection (for AUO test only. Do not connect)
27	NC	No connection (for AUO test only. Do not connect)
28	3D_WP	3D Firmware write protection(Pull low enable)
29	USB GND	USB Ground
30	USB D-	USB D- signal
31	USB D+	USB D+ signal




# Product Specification

M240HTD01.0

AU OPTRONICS CORPORATION

32	GND	Power Ground
33	GND	Power Ground
34	GND	Power Ground
35	GND	Power Ground
36	GND	Power Ground
37	VDD	Power +5V
38	VDD	Power +5V
39	VDD	Power +5V
40	VDD	Power +5V
41	VDD	Power +5V

**Note1:** Start from left side



**Note2:** Input signals of odd and even clock shall be the same timing.



# Product Specification

M240HTD01.0

AU OPTRONICS CORPORATION

## 6.4 Timing Characteristics

Basically, interface timing described here is not actual input timing of LCD module but close to output timing of SN75LVDS82DGG (Texas Instruments) or equivalent.

Signal	Item	Symbol	Min	Typ	Max	Unit
Vertical Section	Period	$T_v$	1125	1180	2047	Th
	Active	$T_{disp(v)}$	1080	1080	1080	Th
	Blanking	$T_{bp(v)}+T_{fp(v)}+PW_{vs}$	45	100	967	Th
Horizontal Section	Period	$T_h$	1034	1060	2047	Tclk
	Active	$T_{disp(h)}$	960	960	960	Tclk
	Blanking	$T_{bp(h)}+T_{fp(h)}+PW_{hs}$	74	100	1087	Tclk
Clock	Period	Tclk	25	13.3	11.1	ns
	Frequency	Freq	40	75	85	MHz
Frame rate	Frame rate	F	46	60	75	Hz

**Note :** DE mode only





## Product Specification

AU OPTRONICS CORPORATION

**M240HTD01.0**

## 6.5 Timing diagram






# Product Specification

M240HTD01.0

AU OPTRONICS CORPORATION

## 6.6 Power ON/OFF Sequence

VDD power and lamp on/off sequence are as follows. Interface signals are also shown in the chart. Signals from any system shall be Hi-Z state or low level when VDD is off.



### Power Sequence Timing

Parameter	Value			Unit
	Min.	Typ.	Max.	
T1	0.5	-	10	[ms]
T2	0	-	50	[ms]
T3	500	-	-	[ms]
T4	100	-	-	[ms]
T5	0	-	50	[ms] Note1,2
T6	5	-	100	[ms] Note1,2
T7	1000	-	-	[ms]

**Note1** : Recommend setting T5 = 0ms to avoid electronic noise when VDD is off.

**Note2** : During T5 and T6 period , please keep the level of input LVDS signals with Hi-Z state.





# Product Specification

M240HTD01.0

AU OPTRONICS CORPORATION

## 7.0 Connector & Pin Assignment

Physical interface is described as for the connector on module. These connectors are capable of accommodating the following signals and will be following components.

### 7.1 TFT LCD Module

Connector Name / Designation	Interface Connector / Interface card
Manufacturer	P-TWO JAE
Type Part Number	187060-4122 FI-RE41S-HF
Mating Housing Part Number	RI-RE41CL/HL

#### 7.1.1 Pin Assignment

Pin#	Signal Name	Pin#	Signal Name
1	RxOIN0-	2	RxOIN0+
3	RxOIN1-	4	RxOIN1+
5	RxOIN2-	6	RxOIN2+
7	GND	8	RxOCLKIN-
9	RxOCLKIN+	10	RxOIN3-
11	RxOIN3+	12	RxEIN0-
13	RxEIN0+	14	GND
15	RxEIN1-	16	RxEIN1+
17	GND	18	RxEIN2-
19	RxEIN2+	20	RxECLKIN-
21	RxECLKIN+	22	RxEIN3-
23	RxEIN3+	24	GND
25	NC (for AUO test only. Do not connect)	26	NC (for AUO test only. Do not connect)
27	NC (for AUO test only. Do not connect)	28	3D Write Protection (Pull low enable)
29	USB GND	30	USB D-
31	USB D+	32	GND
33	GND	34	GND
35	GND	36	GND
37	VDD	38	VDD
39	VDD	40	VDD
41	VDD	-	-



## Product Specification

M240HTD01.0

AU OPTRONICS CORPORATION

### 7.2 Connector on Backlight Unit.

This connector is mounted on LED light-bar.

Connector Name / Designation	Light Bar Connector
Manufacturer	ENTERY
Type Part Number	3707K-Q06N-01

#### 7.2.1 Signal for LED light bar connector

Pin no.	Signal name
1	$I_{LED}$ (current out)
2	$I_{LED}$ (current out)
3	$V_{LED}$ (voltage in)
4	$V_{LED}$ (voltage in)
5	$I_{LED}$ (current out)
6	$I_{LED}$ (current out)



## Product Specification

M240HTD01.0

AU OPTRONICS CORPORATION

### 8.0 Reliability Test

Environment test conditions are listed as following table.

Items	Required Condition	Note
Temperature Humidity Bias (THB)	Ta= 50℃ , 80%RH, 300hours	
High Temperature Operation (HTO)	Ta= 50℃ , 50%RH, 300hours	
Low Temperature Operation (LTO)	Ta= 0℃ , 300hours	
High Temperature Storage (HTS)	Ta= 60℃ , 300hours	
Low Temperature Storage (LTS)	Ta= -20℃ , 300hours	
Vibration Test (Non-operation)	Acceleration: 1.5 Grms Wave: Random Frequency: 10 - 200 Hz Duration: 30 Minutes each Axis (X, Y, Z)	
Shock Test (Non-operation)	Acceleration: 50 G Wave: Half-sine Active Time: 20 ms Direction: ±X, ±Y, ±Z (one time for each Axis)	
Drop Test	Height: 46 cm, package test	
Thermal Shock Test (TST)	-20℃/30min, 60℃/30min, 100 cycles	<b>1</b>
On/Off Test	On/10sec, Off/10sec, 30,000 cycles	
ESD (Electro Static Discharge)	Contact Discharge: ± 8KV, 150pF(330Ω ) 1sec, 15 points, 25 times/ point.	<b>2</b>
	Air Discharge: ± 15KV, 150pF(330Ω ) 1sec 15 points, 25 times/ point.	
Altitude Test	Operation:18,000 ft Non-Operation:40,000 ft	

**Note 1:** The TFT-LCD module will not sustain damage after being subjected to 100 cycles of rapid temperature change. A cycle of rapid temperature change consists of varying the temperature from -20℃ to 60℃, and back again. Power is not applied during the test. After temperature cycling, the unit is placed in normal room ambient for at least 4 hours before power on.

**Note 2:** EN61000-4-2, ESD class B: Certain performance degradation allowed

- No data lost
- Self-recoverable
- No hardware failures.




## Product Specification

**M240HTD01.0**


AU OPTRONICS CORPORATION

### 9.0 Shipping Label

The label is on the panel as shown below:




**Note 1:** For Pb Free products, AUO will add  for identification.


**Note 2:** For RoHS compatible products, AUO will add  for identification.

**Note 3:** For China RoHS compatible products, AUO will add  for identification.

**Note 4:** The Green Mark will be presented only when the green documents have been ready by AUO Internal Green Tea

## 10.0 Mechanical Characteristics









## 11.0 Packing Specification

### 1. Package Follow







## 2. Pallet and shipment information

	Item	Specification			Remark
		Q'ty	Dimension	Weight(kg)	
1	Panel	1	559(H)mm x 324.2(V)mm x 17(D)mm	3	<b>Note 1</b>
2	Cushion	1	-	1.7	
3	Box	1	410(L)mm x 283(W)mm x 655(H)mm	1.2	without Panel & cushion <b>Note 1</b>
4	Packing Box	9 pcs/Box	410(L)mm x 283(W)mm x 655(H)mm	29.9	with panel & cushion <b>Note 1</b>
5	Pallet	1	1140(L)mm x 830(W)mm x 138(H)mm	12	<b>Note 1</b>
6	Pallet after Packing	16 boxes/pallet	1140(L)mm x 830(W)mm x 1448(H)mm	490.4	<b>Note 1</b>

**Note 1:** Estimated value which is subject to change based on real measured data.